

article: Studio BO FR

art. no.: 0018

Studio BO FR is a flame retardant blackout fabric suitable for contract business as well as for a safe home. New up to date blackout fabric with plain appearance (colour matching foam back) and good value for money. Suitable for roller blinds. Vertical blind fabrics on demand.

Fabric characteristics

- flame retardant according to DIN EN 13501
- coated on both sides
- Blockout, colour coordinated back
- suitable for damp rooms
- high light fastness

Manufacturer's processing instructions

When using the fabric "length for drop", we recommend that both edges should be trimmed equally (minimum 5 cm) in order to minimize tension difference.

Technical data

material:	100% PES
no. of colours:	9
width:	2700 mm
roll length:	30 m 33"
thickness:	approx. 0,34 mm / 0.013"
weight:	approx. 255 g/sqm
cutting:	cold cut
weldability:	yes
to be glued:	yes
to be sewed:	yes
care instructions:	can be cleaned with a damp cloth

article: Studio BO FR

art. no.: 0018

Optical data

	Light fastness DIN 54004	reflection %	transmission %	absorption %
0018-001 weiss	≥ 5	76	0	24
0018-002 ecru	≥ 5	70	0	30
0018-003 natur	≥ 5	52	0	48
0018-005 taupe	≥ 5	18	0	82
0018-009 navy	≥ 5	8	0	92
0018-012 hellgrau	≥ 5	35	0	65
0018-013 dunkelgrau	≥ 5	9	0	91
0018-014 greige	≥ 5	33	0	67
0018-015 schwarz	≥ 5	5	0	95

RTA-test range:

visible light 400 – 700 nm, inhouse tests, testing equipment: spectro photometer, in-house-tests.

Tested according to DIN EN 410 (DIN 67507), left side of the fabric.

The technical data for the individual articles are average values obtained from several tests.

Advice offered in this collection card excludes liability for compensation of any sort or any basis.